## **DRILLING RIG INVENTORY**

KIG NUM	Make & Model: LCI-1100 TM  Year Manufactured: 2014  Maximum Depth Rating with 4-1/2" 16.6 ppf. Drill pipe: 14,500  Rotary Drive: Type and Size, Speed Range (rpm): Hacker 22" Speed: 0-150  Approximate number of loads to move rig: 24									
Drawwoi	rks: Main Dru									
		Disc. Assis Make & Mo	st. Brake: 236 odel: WPT	Cable Si	ze: <u>1 ¼"</u>		Number o	f Clutches:2_		
	Sand Dru	m: <b>I</b>	N/A		Cable Size	e: <b>N/A</b>		Cable Length: N/A		
	Engines:	Make & Mo	odel: Qty <u>. (Tw</u>	o) Detroit Serie	s 60 @ 630	HP each. 1260	HP Total			
Derrick:		urer: Number of	LCI Lines:1	0		118' ection Date: New		apacity <u>: 485,000</u> ———		
Top Driv	Manufact		o - HMI 250			n: <u>Top Drive</u> P Power Pack w	/ Detroit Engin	e		
Iron Rou	i <b>ghneck:</b> Manufact	urer: <u>NOV</u>			Model: <u>S</u>	T-80C				
Substruc	Height an	ove base of	f substructure	Rotary 225K S to underside o Yes	f rotary bear	ms <u>: 14'6''</u> No				
Traveling	g Blocks: Make & N	/lodel: <u>Cent</u>	ury		Weight Ca	apacity: <u>250T</u>	Number o	f Lines: <u>10</u>		
Elevator	s: Make &	Model: An	nerican Oil To	ol 250 Ton			<del></del>			
Catwalk:	: Length &	Height: E	Brutus Hydrau	lic Cat Walk						
Pipe Rac	cks: Length	n & Height:_	42" Tall 28' L	.ong						
Drill Pipe						16.6ppf				
Drill Collars: (Minimum quantity required for running manufactures maximum weight on bit for each hole size) Size (O.D. x I.D.): 4.75" or 6.5" Last inspection date & footage since last inspected:  Pumps: Make, Model, Input HP: (2) TFI F-1600 Engine Make & Model: Cat Model 3512										
	Liner Size and Stroke Length: 6.5"X 12"  Max. Continuous Operating Pressure: 4200 PSI  Pump Speed (spm): 120									
Steel Mu	Dimensio Shale Sha	aker Make &	& Model: (2) D	VIDE X 43'_LC terrick 504 5 Magnum Cen			BLS Number	of Compartments <u>:7</u> 		
BOP's:		/lodel: <u>Shaff</u> Rating:3				Date	Size: <u>11"</u> of Last Inspec	tion: Current		
Rotating	Head:		odel: Washing							
Accumu	Make & N Capacity Number of Hydraulic	Model: E of Hydraulic of Stations: Pressure S Electric Mo Gas/Diese ulic Pump:	Burnsco Bison c Fluid: 250 5 Source: 650	Gal Triplex Cat Pu Explosion Proof	mp_	Number of Pres		6		
Choke M										
	Valves:	Pressure F Date of Las	odel: Camero Rating & Size: st Inspection: odel: PO8RS	3000psi /3" Current				Type: Adjustable		
		Pressure F		5000psi size 2	1/16"					
Light Pla	ant:	20	- p							
	Voltage, A		Watts: 480/ el <u>: Detroit Seri</u>	/240 500KW es 60						
Drilling F		Model: <u>Paso</u> be:		<b>X</b> 24 Hou	r					